

# AXS-200

part of the SharpTESTER Access Line

NETWORK TESTING – ACCESS



**The new authority in access network testing:  
designed for multilayer testing on both  
copper and optical fiber**

## Efficiency and Simplicity

- One-touch test start/stop
- A single user interface for all SharpTESTER series modules
- Flexible architecture adapting to evolving customer requirements
- Rugged, weather-proof design
- Easy to use, even for technicians who are inexperienced or unfamiliar with specific applications
- Fast and clear pass/fail results on a transreflective graphical color display

## A Multilayer, Multimedium Test Solution– Three Module Series

### Copper/DSL/Triple-Play

- Complete local loop testing
- xDSL QoS assessment of triple-play services
- Ethernet testing for triple-play services

### Optics

- Physical-layer testing within fiber access links

### Ethernet

- Installation and maintenance testing for Ethernet circuits

## Flexible Connectivity

- Easy file transfer and software upgrade through USB connection
- USB A/B and RJ-45
- Fiber inspection probe port



Next-Generation Network Assessment

**EXFO**  
EXPERTISE REACHING OUT

überreicht durch:  
**Opternus**

Opternus GmbH Optische Spleiss- & Messtechnik  
Bahnhofstr. 5  
D-22941 Bargteheide  
Tel. +49(0)4532-20 44-0  
Fax +49(0)4532-20 44-25  
E-Mail: [Info@Opternus.de](mailto:Info@Opternus.de) - [www.Opternus.de](http://www.Opternus.de)

Büro Süd:  
Wäldenbronner Str. 2  
D-73732 Esslingen  
Tel. +49(0)711-3 10 59 99-0  
Fax +49(0)711-3 10 59 99-99

### SPECIFICATIONS

Display	89 mm (3.5 in) LCD, 320 x 240, QVGA, advanced TFT
Interfaces	USB host/client, RJ-45 Ethernet 10/100, video fiber inspection probe port
Storage	Internal: 512 MB; USB: 1 GB, 2 GB and more
Battery	Smart rechargeable Li-Ion
Power supply	15-24 VDC, 40 W minimum

### GENERAL SPECIFICATIONS

Temperature	operating	-10 °C to 50 °C	(14 °F to 122 °F)
	storage <sup>a</sup>	-40 °C to 70 °C	(-40 °F to 158 °F)
Size (H x W x D)	241 mm x 109 mm x 38 mm	(9 1/2 in x 4 5/16 in x 1 1/2 in)	
Weight	0.47 kg	(1.0 lb)	
Relative humidity	0 % to 93 %, non-condensing		
Warranty	1 year		

**Note**

a. Maximum of 60 °C (140 °F) for the internal battery.

### ACCESSORIES

GP-10-072	Semi-rigid carrying case
GP-10-074	Rigid carrying case AXS-200
GP-2016	RJ-45 LAN cable (10 feet)
GP-2019	USB microdrive (1 GB)

### ORDERING INFORMATION

#### AXS-200-XX-XX

**Model** ■

AXS-200 = SharpTESTER

**Probe option** ■

00 = Without probe

FP4S = Inspection probe (400x)

FP4D = Inspection probe (200x/400x)

■ **Platform software option**

FPS = With FIP software

Example: AXS-200-FP4D-FPS

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: +1 418 683-0211 | Fax: +1 418 683-2170 | info@EXFO.com

Toll-free: +1 800 663-3936 (USA and Canada) | [www.EXFO.com](http://www.EXFO.com)

<b>EXFO America</b>	3701 Plano Parkway, Suite 160	Plano, TX 75075 USA	Tel.: +1 800 663-3936	Fax: +1 972 836-0164
<b>EXFO Asia</b>	151 Chin Swee Road, #03-29 Manhattan House	SINGAPORE 169876	Tel.: +65 6333 8241	Fax: +65 6333 8242
<b>EXFO China</b>	No. 88 Fuhua First Road Central Tower, Room 801, Futian District	Shenzhen 518048 P. R. CHINA	Tel.: +86 (755) 8203 2300	Fax: +86 (755) 8203 2306
	Beijing New Century Hotel Office Tower, Room 1754-1755 No. 6 Southern Capital Gym Road	Beijing 100044 P. R. CHINA	Tel.: +86 (10) 6849 2738	Fax: +86 (10) 6849 2662
<b>EXFO Europe</b>	Omega Enterprise Park, Electron Way	Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel.: +44 2380 246810	Fax: +44 2380 246801
<b>EXFO Service Assurance</b>	285 Mill Road	Chelmsford, MA 01824 USA	Tel.: +1 978 367-5600	Fax: +1 978 367-5700

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit [www.EXFO.com/recycle](http://www.EXFO.com/recycle). Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at <http://www.EXFO.com/specs>

In case of discrepancy, the Web version takes precedence over any printed literature.