



No.: B-08F0017  
Date of issue: Mar. 26, 2008

**DATA SHEET**

***Thermal Jacket Stripper HJS-02***

*For fiber ribbon splice application*



**HJS-02**

The HJS-02 is designed for stripping of fiber ribbon with up to 12 fibers all together. In order to achieve this, the HJS-02 is equipped with a heater, which softens the coating of the fiber ribbon for smooth stripping.

SPECIFICATIONS	
Applicable fiber count	1 to 12 fibers
Coating material	UV cured resin
Thickness of the fiber ribbon	250 to 400 um
Coating / Cladding diameter	250 / 125 um
Stripping length	Max. 35 mm
Heating time	Approx. 3 sec. at normal mode, Approx. 8 sec. at power saving mode
Power supply	12 V DC from Fujikura splicer with DC power cord 85 to 265 V AC with optional AC adapter.
Fiber setting	by FH-60 / 50 series Fiber Holder, except FH-60-900, FH-50-250 and FH-50-900
Dimensions, Weight	107W x 40D x 29H mm, 195g

STANDARD PACKAGE		
Description	Model	Q'ty
Stripper main body	HJS-02	1 pc.
DC power cord for FSM-50R/17R	DCC-11	1 pc.
Cleaning brush	BRS-01	1 pc.
Hexagonal wrench	-	1 pc.
Instruction manual	-	1 pc.



OPTIONAL ITEMS	
Description	Model
AC adaptor	ADC-09
AC power cord	ACC-08 ~ -12
DC cord for FSM-30R / -16R	DCC-02, -03

FIBER HOLDERS								
Fiber	Single (250µm)	2-fiber ribbon	4-fiber ribbon	5-fiber ribbon	6-fiber ribbon	8-fiber ribbon	10-fiber ribbon	12-fiber ribbon
Model	FH-60-250	FH-50-2	FH-50-4	FH-50-5	FH-50-6	FH-50-8	FH-50-10	FH-50-12

Specifications and descriptions are subject to change without prior notice.