



Netzwerk-Protokolltester

	Modell / Anwendung	BV-10 (Remote)	FTB-5245 (OSA)	FTB-5255 (OSA)	FTBx-88260	FTBx-88480	FTBx-88460	FTBx-88810/11	FTBx-8880	FTBx-8870	Max-860	Max-860G	Max-880	Max-890	Max-890Q	Max-940
Eigenschaften	PDH (E1/DS1/DS3)								•				•			
	Sonet/SDH								•	•			•	•	•	
	OTN						•		•	•			•	•	•	
	NGN / EoS															
	Ethernet	•			•	•	•	•	•	•	•	•	•	•	•	•
	Loopback-Gerät/Prüfkopf	•														
	Fibre Channel				•			•	•	•				•	•	•
	WDM Layer Tests		•	•												
	IPv6 Tests				•	•		•	•	•	•	•	•	•	•	•
	Open Transceiver System (OTS)				•	•	•	•								•
PDH/DSn	E1								•				•	•	•	
	E2, E3, E4								•				•	•	•	
	DS1, DS3								•				•	•	•	
SDH/SONET	STM-0e, STM-1e								•	•			•	•	•	
	STM-1, 4, 16				•				•	•			•	•	•	
	STM-64				•				•	•			•	•	•	
	STM-256													•	•	
OTN	OTU1				•	•	•	•	•	•			•	•	•	
	OTU2				•	•	•	•	•	•			•	•	•	
	OTU3				•	•	•	•						•	•	
	OTU4				•	•	•	•						•	•	
	OTUCn/FlexO				•	•	•	•	•	•						
NGN	VCAT, CAS, GFP															
Ethernet	10 / 100 / 1000 Base-T	•			•				•	•	•	•	•	•	•	
	GigE	•			•	•	•	•	•	•	•	•	•	•	•	•
	10 GigE				•	•	•	•	•	•		•	•	•	•	•
	40/100GigE				•	•	•	•						•	•	•
	25/50GigE				•	•	•	•								•
	400GigE					•	•	•								•
	800GigE					•	•	•								
Fibre Channel	FC-1x, FC-2x				•			•	•	•				•	•	•
	FC-4x				•			•	•	•				•	•	•
	FC-8x				•			•	•	•				•	•	•
	FC-10x				•			•	•	•				•	•	•
	FC-16x				•			•								•
	FC-32x				•			•								•
	FC-64					•		•								
	Carrier E / SyncE / 1588				•	•		•	•	•						•
	CPRI (FTTA)				•				•	•						
	Kabeltests								•	•	•	•	•			
	Transceivertest (iOptics)				•	•	•	•	•	•				•	•	•
	iSAM (ITU-T Y.1564) bis 100G				•	•	•	•	•	•				•	•	•
	RFC 2544				•	•	•	•	•	•	•	•	•	•	•	•