



High Precision Fiber Stripper HTS-12



HTS-12

The HTS-12 is designed for stripping single count of silica optical fiber by keeping the stripped fiber's glass surface free from any physical contact.

In order to achieve the above condition, the HTS-12 has a precise linear slide base for stripping action. The fiber is not scuffed by the blade or any other materials when being stripped. The HTS-12 is equipped with a heater to soften the fiber coating.

The HTS-12 accepts the FH-40 series and FH-100 series Fiber Holder System.

STANDARD PACKAGE			SPECIFICATIONS	
Description	Model	Q'ty	Fiber count	Single
Stripper main body	HTS-12	1pc.	Fiber type	Silica optical fiber
Blades for 250 μ m	HTS-CT-250	1pc.	Coating material	UV cured resin
AC adapter	ADC-08	1pc.	Cladding diameter	125 μ m
AC power cord	ACC-08~12	1pc.	Coating diameter	250 μ m, 400 μ m, with optional blade
Cleaning brush	BRS-1	1pc.	Stripping length	Max. 35mm
Instruction manual	-	1pc.	Heating time	Approx. 3sec.
			Temperature setting	120, 140, 160, 180 degrees C, adjustable
			Fiber placing	With FH-40 series and FH-100 series Fiber Holder
			Power supply	100 to 240V AC / 50 to 60Hz with ADC-08
			Voltage polarity	Positive $\ominus \bullet \oplus$
			Dimensions, Weight	140W x 60D x 60H mm, 600g
			OPTIONAL ITEMS	
			Description	Model
			Blades for 400 μ m	HTS-CT-400
			Grease for blade setting	HTS-GREASE

HTS-12



Note) The export of HTS-12 is controlled under Foreign Exchange and Foreign Trade Law of Japan.
Therefore, your order shall be subject to the approval of the Japanese Government.

No.: B-12M0065A
Date of issue: Nov. 1, 2014

Änderung der technischen Daten und des Lieferumfangs jederzeit ohne Vorankündigung möglich.

überreicht durch:

Opternus

Opternus GmbH Optische Spleiss- & Messtechnik

Bahnhofstr. 5
D-22941 Bargteheide

Tel. +49(0)4532-20 44-0
Fax +49(0)4532-20 44-25

Büro Süd:

Katharinenstr. 57
D-73728 Esslingen

Tel. +49(0)711-3 10 59 99-0
Fax +49(0)711-3 10 59 99-99

E-Mail: info@opternus.de - www.opternus.de - www.opternus-shop.de

Änderung der technischen Daten und des Lieferumfangs jederzeit ohne Vorankündigung möglich.

überreicht durch:

Opternus GmbH Optische Spleiss- & Messtechnik

Büro Süd:

Bahnhofstr. 5
D-22941 Bargteheide

Tel. +49(0)4532-20 44-0
Fax +49(0)4532-20 44-25

Katharinenstr. 57
D-73728 Esslingen

Tel. +49(0)711-3 10 59 99-0
Fax +49(0)711-3 10 59 99-99

E-Mail: info@opternus.de - www.opternus.de - www.opternus-shop.de

