

Polyimide Coating Stripper


Fujikura

ARC Master™

PCS-100



Features

- Quick stripping of minimum 20sec / fiber
- Mechanical stripping with chemical-free operation.
- Safer and quality stripping with no oxidization by burning.
- Adjustable parameters for various fiber coatings.
- Mechanical fiber proof tester.



Specifications and descriptions are subject to change without prior notice.

überreicht durch:



Opternus GmbH Optische Spleiss- & Messtechnik

Bahnhofstr. 5
D-22941 Bargteheide

Tel. +49(0)4532-20 44-0
Fax +49(0)4532-20 44-25

Büro Süd:

Katharinenstr. 57
D-73728 Esslingen

Tel. +49(0)711-3 10 59 99-0
Fax +49(0)711-3 10 59 99-99

E-Mail: info@opternus.de - www.opternus.de - www.opternus-shop.de

SPECIFICATION

Description	APM-100
Applicable fiber	Conventional silica optical fiber
Fiber count	Single fiber
Cladding diameter	φ 60 to 1200 μm
Fiber holder	FH-100-xx
Coating diameter	φ 60 to 1500 μm
Stripping length	1 to 35mm
Stripping time	Coating removing action × 4 : 20 sec Coating removing action × 8 : 35 sec Coating removing action × 12 : 50 sec
Blade life	350 fibers (coating removing action × 4)
Dimension	230 (W) × 214 (D) × 151 (H) mm
Weight	5 kg
Power supply	External AC adapter : ADC-15 Input : AC100 to 240 V (50 to 60Hz) (max. 80W AC)
Operating condition	0 to 95%RH and 0 to 40 degC (non-dew)
Storage condition	0 to 95%RH and -40 to 80 degC (non-dew)

STANDARD PACKAGE



STANDARD PACKAGE

Description	Model	Qty.	Note
Polyimide coating stripper	PCS-100	1pc	
AC adapter	ADC-15	1pc	
AC power cord	ACC-**	1pc	
Fiber holder	FH-100-150	1pair	
Instruction manual	M-PCS100-E	1pc	
Blade	PCB-01	1pc	50 pcs / box For replacement
Hexagonal wrench	HEX-01	1pc	For blade replacement

OPTIONAL ITEMS


Item	Description	Note
Fiber Holder	FH-100-***	Fiber Holder for FSM-100 series *** : Coating diameter 060, 100, 125, 150, 180, 210, 250, 300, 350, 400, 500, 600, 700, 800, 900, 1000, 1100, 1200, 1300, 1400, 1500, 1600, 1700, 1800, 1900, 2000 μm
	FH-100-***-EV	-EV is Fiber Holder for End-view observation system
Blade	PCB-01	50 pieces of 1 box, for replacement

1. Set



Set fiber.

2. Stripping



Coating is peeled off with stripping blade.

3. Proof test



Transfer the fiber to the proof test unit.

Specifications and descriptions are subject to change without prior notice.

überreicht durch:

Opternus

Opternus GmbH Optische Spleiss- & Messtechnik

Bahnhofstr. 5
D-22941 Bargteheide

Tel. +49(0)4532-20 44-0
Fax +49(0)4532-20 44-25

Büro Süd:

Katharinenstr. 57
D-73728 Esslingen

Tel. +49(0)711-3 10 59 99-0
Fax +49(0)711-3 10 59 99-99

E-Mail: info@opternus.de - www.opternus.de - www.opternus-shop.de