



MINI DRUM RACK

For easy, safe and effective roll out of micro fiber

Safe roll out of fiber

A drum safely attached to a drum rack with cones and ball bearings creates better fiber blowing results as it protects the fiber.

Equipped with brakes

The mini drum rack is equipped with effective brakes, to avoid fiber overflow disrupting the fiber blowing job.

Easy management and transportation

The drum rack has small wheels making it easy to transport. Furthermore, you can easily fold it minimizing its size so it is possible to transport in small cars.

Flexible lock function

During transport, you can utilize the lock function on the rack handle to secure the drum and thus the fiber.

COMPATIBLE WITH

NanoFlow (Item No.: 101-160601800)
• For fibers 0.8-3.0 mm

NanoFlow MAX (Item No.: 101-190911001)
• For fibers 0.8-4.5 mm

MicroFlow TOUCH (Item No.: 101-10051)
• For microfibers 0.8-6.5 mm

MicroFlow LOG (Item No.: 101-171001001)
• For microfibers 0.8-6.5 mm

SPECIFICATIONS

Item No.:	103-201112002
Drum diameter:	610 mm
Drum center diameter:	20-83 mm
Max. drum width:	443 mm
Max. drum weight*:	70 kg
Weight:	7.7 kg
Length:	557 mm
Width:	490 mm
Height:	842 mm

*With cable drums above 50 kg, the support arm delivered together with the drum rack must be used.

Specifications and descriptions are subject to change without prior notice.



Opternus GmbH Bahnhofstr. 5 • D-22941 Bargtheide • Tel. +49(0)4532-20 44-0 • Fax -25 • E-Mail info@opternus.de • www.opternus.de

©Opternus GmbH 2021-01