



Fiber Holder FH-60 series



The FH-60 series single fiber holder and FH-FC series cable fiber holder are exclusively used for Fujikura 70 series, 22 series, 12 series, and former Fujikura Splicers.

The Fujikura Fiber Holder System is developed to provide appropriate splicing work for several kinds of fibers, 250um fiber, 900um fiber, loose tube fiber, drop cable, 3mm cable or 2mm cable.

The FH-60 series and FH-FC-30 are supplied with a pair, for the left and the right respectively.

As for fiber holder for ribbon fiber, please see FH-50 series datasheet.

SPECIFICATION			FH-60-250&900	FH-60-LT900, FH- FC-20&30		
Applicable number of fiber			Single			
Type variation			In accordance with outside diameter of fiber Please see VARIATION table below			
Fiber holding			Magnetic clamping			
Fiber Holder placing onto splicer			Guide-pin system with two pins per one side of Fiber Holder			
Dimensions			38L x 16W x 7H [mm]	41L x 18W x 8H [mm]		
Weight			20g for 1pair	22g for 1pair		
Material			Base plate: Heat-hardening plastic / Lid: Iron-Nickel alloy			
Use for	Arc Fusion Splicer	Single	70S, 19S, 12S and former Fujikura single fiber splicer			
		Ribbon	70R, 19R, 12R and former Fujikura mass fiber splicer			
	Fiber Cleave	r	CT-30, CT-05			
	Jacket Stripp	er	HJS-02, HJS-03 (FH-60-250 only)			


VARIATION											
Model	FH-60-250	FH-60-900	FH-60-LT900	FH-60-DC250	FH-FC-30	FH-FC-20					
Fiber	Single (250µm)	Single (900µm)	Loose Tube Single Fiber (900µm)	Drop Cable Single(250um)	3mm Cable	2mm Cable (Left only)					

Note) The FH-60 series can be used for Fujikura former models of splicers or fiber cleavers.

Specifications and descriptions are subject to change without prior notice.

Bahnhofstr. 5

D-22941 Bargteheide



Opternus GmbH Optische Spleiss- & Messtechnik

Tel. +49(0)4532-20 44-0 Fax +49(0)4532-20 44-25 Katharinenstr. 57 D-73728 Esslingen Tel. +49(0)711-3 10 59 99-0

Fax +49(0)711-3 10 59 99-99